

SELECT DOUBLE HUNG WINDOW



Features & Benefits

- New design removed visible drainage screen notch for an elegant look
- Sloped sill for improved water performance and historic colonial appearance
- New and improved weep notches
- Improved Structural/Performance and Thermal Ratings
- Equal sash sizes for optimum glass area
- Can be mulled with other systems
- Snap-in screen support
- Available in any brickmould style
- Full screen & half screen are available
- New Integral 3/4" return available
- Available in white uPVC only
- All standard paint colors or custom paint colors available for exterior
- 3/4" Glass thickness
- Available in 3 1/4" frame size
- NAFS, NFRC and CSA Certified

Select's Key Features

- Dual glazed Low-E, Low-E Argon and Energlass glass available
- Standard grille options
- Slimline sash, lock & keeper
- Spiral Balance System
- 30 Year Warranty



SELECT REDEFINED NEW LOOK, BETTER PERFORMANCE

We've upgraded our Select Double Hung window to offer optimum performance with a sleeker frame. Our new design offers improved thermal ratings (ER & U values), improved structural/performance ratings, and a smooth, elegant profile.

Performance Ratings

Window Type	Tested Size	Performance Grade (PG)	Design Pressure	Water Penetration Resistance	Canadian Air Leakage
Operator	48" x 72"	35	+/- 1680 Pascals	360 Pascals	A2
Picture	72" x 80"	55	+/- 2640 Pascals	730 Pascals	Fixed

Thermal Ratings

Glass Options	Energy Ratings	U-value (Metric)	U-value (Imperial)	Solar Heat Gain Coefficient	Visible Transmission	Condensation Resistance	Canadian Energy Star Zones
Energlass-LSG	20	1.65	0.29	0.30	0.55	58	N/A
LoE/Argon-LSG	19	1.70	0.30	0.30	0.55	55	N/A
Energlass	33	1.70	0.30	0.55	0.63	53	1,2
LoE/Argon	32	1.76	0.31	0.55	0.63	54	1,2

