


Calculation based on ISO 15099

Product name: <b>Kohltech CPVC Inswing Door FX Sidelite</b>			Center-of-glass properties					
ASHRAE/IECC /DOE North American Climate Zone	North, East, West - facing	South- facing			Guardian 1.0 OA-CG7036#2-Arg95- CG7036#4-Arg95-Clr No Grids			
Climate specific recommendations:					Whole-window installed U-value		Ucog-Value	
			W/m2K	BTU/hr.ft2.F	SHGC	W/m2K	BTU/hr.ft2.F	
8			1.31	0.23	0.303	0.936	0.165	
7			1.31	0.23	0.303	0.943	0.166	
6			1.32	0.23	0.303	0.953	0.168	
5			1.32	0.23	0.303	0.956	0.168	
4			1.32	0.23	0.303	0.961	0.169	
Marine North			1.33	0.23	0.303	0.964	0.170	
Marine South			1.33	0.23	0.303	0.969	0.171	
3			1.33	0.23	0.303	0.966	0.170	
2 West			1.33	0.23	0.303	0.971	0.171	
2 East			1.33	0.23	0.303	0.971	0.171	
Kohltech CPVC Inswing Door Premium Plus ZF-S	FRAME				Psi-spacer		Psi-opaque	
	Frame height		U-frame		Ψ		W/mK	
	mm	in	W/m2K	BTU/hr.ft2.F	W/mK	BTU/hr.ft.F		
	Head	111	4.35	1.62	0.29	0.020	0.011	0.243
	Sill	147	5.79	1.86	0.33	0.019	0.011	BTU/hr.ft.F
left jamb	111	4.35	1.62	0.29	0.021	0.012	0.140	
right jamb	111	4.35	1.62	0.29	0.021	0.012	Grade D	

Valid through June 2023