



Phius Product Number: D-100147
Date Last Certified: 08/15/2023
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through:
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Kohltech cPVC Inswing Door FX Sidelite

Manufacturer: Kohltech Windows & Entrance Systems

Primary Frame Material: Vinyl

Series: cPVC

Operation Category: Swinging Door

Model: cPVC Inswing Door FX Sidelite

Operation Type: Single Swinging Door

NFRC CPD #: KOI-A-36-136392-00001

IGU DETAILS

Glazing Name: 7036 surfaces 2 & 4, Arg95, 1" OA

Glass Layers: Triple

Gas Fill: Argon

Spacer Model: Quanex Super Spacer Premium Plus

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Door U-values by Zone, at Standard Model Size [Btu/hr·ft²·°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓		✓				
U-Whole-Door	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22	0.22

Modeled Size [W × H] 37.80" × 82.28"

SHGC, Whole Door: 0.20

Condensation Resistance:

COMPONENT-LEVEL PERFORMANCE DATA [IP Units] | *Compatible with building energy modeling tools*

U-COG | Center of Glass U-Values, by Climate Zone [Btu/hr·ft²·°F]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.16

SHGC-COG | Center of Glass Solar Heat Gain Coefficient, All Climate Zones

0.30

Frame Parameters	Left Jamb	Right Jamb	Left Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	4.37"	4.37"	4.37"	5.79"
Frame U-Value [Btu/hr·ft ² ·°F]	0.29	0.29	0.29	0.33
Glazing-to-Frame Psi Value [Btu/hr·ft·°F]	0.0120	0.0120	0.0113	0.0109

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)



Phius Product Number: D-100147
Date Last Certified: 08/15/2023
THERM Files Available: No

Phius Certification Path: Blue Path
Valid Through:
Air Leakage Test Data Available: No



PRODUCT INFORMATION

Product Name: Kohltech cPVC Inswing Door FX Sidelite

Manufacturer: Kohltech Windows & Entrance Systems

Primary Frame Material: Vinyl

Series: cPVC

Operation Category: Swinging Door

Model: cPVC Inswing Door FX Sidelite

Operation Type: Single Swinging Door

NFRC CPD #: KOI-A-36-136392-00001

IGU DETAILS

Glazing Name: 7036 surfaces 2 & 4, Arg95, 1" OA

Glass Layers: Triple

Gas Fill: Argon

Spacer Model: Quanex Super Spacer Premium Plus

RECOMMENDED CLIMATE ZONES (NOTE: This information is not for use in building energy models. See next section.)

Recommended Climate Zones and Whole-Door U-values by Zone, at Standard Model Size [W/m²K]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
Recommended Zones	✓	✓	✓	✓		✓				
U-Whole-Door	1.25	1.25	1.25	1.25	1.24	1.25	1.24	1.24	1.23	1.23

Modeled Size [W × H] 0.96 m × 2.09 m **SHGC, Whole Door:** 0.20 **Condensation Resistance:**

COMPONENT-LEVEL PERFORMANCE DATA [SI Units] | *Compatible with building energy modeling tools*

U-COG | Center of Glass U-Values, by Climate Zone [W/m²K]

Climate Zone	0, 1, 2	3A	3B	3C	4A, 4B	4C, 5C	5A, 5B	6	7	8
U-COG Value	0.97	0.97	0.97	0.97	0.96	0.96	0.96	0.95	0.94	0.94

SHGC-COG | Center of Glass Solar Heat Gain Coefficient, All Climate Zones

0.30

Frame Parameters	Left Jamb	Right Jamb	Left Head	Sill
Frame Section	Left	Right	Top	Bottom
Frame Width	111 mm	111 mm	111 mm	147 mm
Frame U-Value [W/m ² K]	1.62	1.62	1.62	1.86
Glazing-to-Frame Psi Value [W/mK]	0.0208	0.0208	0.0196	0.019

Frame-to-Wall Psi Value is dependent on the on-site installation condition. (See Phius Guidebook for more details.)